



Success with 2009 IECC in South Carolina:
Checklists for Builders

FOUNDATION





JOB READY: FOUNDATION

Success with 2009 IECC in South Carolina for Builders



N/A



1. Work site is clean and construction materials are properly stored before proceeding.

Builder Verification



Stop work until details are corrected.



Proceed without corrections.

The sub-contractor who signs and completes this form is doing so to the best of his/her knowledge and should not be held legally responsible for work completed by other organizations. The intent of this form is to ensure job sites are ready before beginning work.

Signature

Date



JOB COMPLETE:

FOUNDATION

Success with 2009 IECC in South Carolina for Builders



N/A



1. For crawlspaces, install poly sheeting that is at least 6-mil thickness and overlaps at least 6 inches.



2. Damp proof the exterior of all below-grade walls.



3. Install a drainage system along entire foundation footing of below-grade walls.



4. Install exterior slab insulation without gaps, voids, misalignments or compression and with a rigid, opaque and weather-resistant protective covering.



5. Install exterior insulation levels to meet the 2009 IECC.



6. Ensure work site is clean and construction materials are properly stored before proceeding.

Certification

The sub-contractor who signs and completes this form is doing so to the best of his/her knowledge and should not be held legally responsible for work completed by other organizations. The intent of this form is to ensure job sites are ready before beginning work.

Name

Company

Signature