



Success with 2012 Code:
Checklists for Builders

FOUNDATION





JOB READY: FOUNDATION

Success with 2012 IECC for Builders



N/A



1. Work site is clean and construction materials are properly stored before proceeding.

Builder Verification



Stop work until details are corrected.



Proceed without corrections.

The sub-contractor who signs and completes this form is doing so to the best of his/her knowledge and should not be held legally responsible for work completed by other organizations. The intent of this form is to ensure job sites are ready before beginning work.

Signature

Date



JOB COMPLETE:

FOUNDATION

Success with 2012 IECC for Builders

✓	✗	N/A	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	1. For crawlspaces, install 6-mil poly sheeting to overlap and extend up foundation walls at least 6 inches.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	2. Damp proof the exterior of all below-grade walls.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	3. Install a drainage system along entire foundation footing of below-grade walls.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	4. For exterior insulation, install without gaps, voids, misalignment or compression and with a rigid, opaque and weather resistant protective covering.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	5. For exterior insulation, install to meet 2012 IECC insulation levels.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	6. Ensure work site is clean and construction materials are properly stored before proceeding.

Certification

The sub-contractor who signs and completes this form is doing so to the best of his/her knowledge and should not be held legally responsible for work completed by other organizations. The intent of this form is to ensure job sites are ready before beginning work.

Name

Company

Signature